sSection 1: Product and Company Identification

	_, Inc. Telep ver Avenue r, WI 54880	hone: CHEMTREC (Spill Emergency Only): 1-800-424-9300 Information: 715-392-7101
--	--	---

AMSOIL Product Code	TCR
Product Label Name	Series 2000 2-Cycle Racing Oil
Product Use	LUBRICATING OIL

Section 2: Composition/Information on Ingredients

This product is not formulated to contain ingredients that have exposure limits exceeding those established by US agencies.

\*See Section 8 for exposure limits.

Section 3: Hazards Identification

POTENTIAL HEALTH EFFECTS: Minor eye and skin irritant.

Section 4: First Aid Measures


- EYE: Flush with water for 15-20 minutes. Seek medical attention if irritation develops.
- SKIN: Wash immediately with soap and water. Remove contaminated clothing and launder before reuse. Discard shoes and leather articles saturated with the product. Obtain medical advice if irritation occurs.
- INHALATION: Remove exposed person to fresh air. If breathing is labored give oxygen. If breathing has stopped apply artificial respiration. Get immediate medical attention.
- INGESTION: DO NOT INDUCE VOMITING. If conscious, give 2 glasses of water. If vomiting does occur, keep head below hips to reduce risk of aspiration. Get immediate medical attention.

Section 5: Fire Fighting Measures

FLAMMABILITY PROPERTIES:	Flash Point	176°F(80°C)
	Method	
	LFL/UFL	Not Determined
	Auto-ignition Temperature	Not Determined

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, and alcohol foam.

FIREFIGHTING EQUIPMENT: Full bunker gear recommended including a positive pressure self-contained breathing apparatus.



# Section 6: Accidental Release Measures

Isolate spill area. Provide adequate ventilation. Wear appropriate personal protection. Recover free product for recycle and/or disposal. Add sand, earth or other suitable absorbent to spill area. Prevent entry into sewers and waterways. Check under Transportation and Labeling (DOT/CERCLA) and Other Regulator Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spill.

#### Section 7: Handling and Storage

HANDLING: Keep containers closed. Avoid contact with eyes, skin or clothing. Wash hands after handling. Empty container may retain product residue which may exhibit hazards of product.

STORAGE: Keep away from heat or flame.

#### Section 8: Exposure Controls/Personal Protection

VENTILATION: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.

RESPIRATORY: Use a NIOSH approved respirator when necessary.

SKIN: Use Viton or Nitrile gloves to avoid prolonged or repeated skin contact.

EYE: Use splash goggles or face shield where splashing is expected or can occur.

EXPOSURE LIMITS: The Threshold Limit Value (TLV) of 5 mg/m<sup>3</sup> is suggested for oil mist.

# Section 9: Physical and Chemical Properties

Physical State	Liquid
Boiling Point	Not Determined
Freezing/Melting Point	
Vapor Pressure	
Vapor Density (Air=1)	Not Determined
Evaporation Rate	Not Determined
Solubility in Water	Insoluble
Specific Gravity (Water=1)	0.8816
Density, lb./gal	7.341
Volatility (Volume)	Unknown
VOC	Unknown
Volatility (Volume) VOC pH	Not Determined
Coefficient of Water/Oil Distribution	Not Determined
Odor	
Odor Threshold	
Appearance	Red Transparent Liquid
Viscosity, cSt @ 100°C	
Viscosity, cSt @ 40°C	
Viscosity Index	

# Section 10: Stability and Reactivity

STABILITY: Stable under moderately elevated temperatures and pressures.

INCOMPATIBILITY: Avoid contact with strong oxidants

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION OF PRODUCT: Toxic oxides of carbon, aldehydes and other products of incomplete combustion.

Section 11: Toxicological Information

# ACUTE EXPOSURE Eye Irritation: Moderate to strong eye irritation. Based on data from components or similar material. Skin Irritation: Not expected to be a primary skin irritant. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, defatting, and cracking of the skin. **Respiratory Irritation:** If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract similar to that observed with mineral oil. Based on data from components or similar materials. Under good industrial hygiene practices where all exposure limits are observed, respiratory irritation should not be a problem. CHRONIC EXPOSURE Chronic Toxicity: No data available to indicate product present at greater than 1.0% are chronic health hazards. Carcinogenicity: No data available to indicate product present at greater than 0.1% are a carcinogenic hazard. Mutagenicity: No data available to indicate product present at greater than 1.0% present a mutagenic or genotoxic hazard. **Reproductive Toxicity:** No data available to indicate product present at greater than 1.0% present a reproductive hazard. No data available to indicate product present at greater than 1.0% present a Teratogenicity: teratogenic hazards. ADDITIONAL INFORMATION

Exposure Limits: Under conditions which may generate mists, observe the OSHA PEL of 5 mg per cubic meter, ACGIH STEL of 10 mg per cubic meter.

# Section 12: Ecological Information

No data available on the adverse effects of this product on the environment.

# Section 13: Disposal Considerations

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261

#### Section 14: Transport Information

This product is not classified as hazardous material for DOT shipping. For further information relative to spills resulting from transportation incidents, refer to the latest DOT Emergency Response Guidebook for Hazardous Materials.

#### Section 15: Regulatory Information

U.S. Federal Regulations

OSHA Table ZSy	nthetic Base Stock (mist)
TSCA	Not Applicable
CERCLA 40 CFR 302.4	Not Applicable
SARA Title III	
Section 302 Extremely Hazardous	Not Applicable
Section 311/312	
Fire Hazard	
Reactive Hazard	
Release of Pressure	
Acute Health Hazard	Yes
Chronic Health Hazard	No
Section 313 Toxic Chemical	Not Applicable

# U.S. State Regulations

California (Prop 65)

Does not contain chemicals known to the state of California to cause cancer.

# International Regulations

WHMIS .....All components listed

#### Section 16: Other Information

The information and recommendations contained herein are, to the best of AMSOIL's knowledge and belief, accurate and reliable as of the date issued. AMSOIL makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and AMSOIL shall not be liable for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with AMSOIL's interpretation of the available data.